

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond CSA - Liquid

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond CSA - Liquid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Activator.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone UK +44 (0)1962 711 661 USA 0800 640 7599 Asia +86 (0)21 5773 4913

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Human health In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Environmental Toxic to aquatic life with long lasting effects.

Physicochemical The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

2.2. Label elements

Pictogram



Signal word

Danger

Permabond CSA - Liquid

Hazard statements	H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P302+P352a IF ON SKIN: Wash with plenty of soap and water P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Contains	HYDROCARBONS, C7, n-ALKANES, ISOALKANES, CYCLICS
Supplementary precautionary statements	P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves, eye and face protection. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with existing Community, National and local regulations.

2.3. Other hazards

None under normal conditions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBONS, C7, n-ALKANES, ISOALKANES, CYCLICS	60-100%
CAS number: —	EC number: 927-510-4
	REACH registration number: 01-2119475515-33-XXXX
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
trans-DICHLOROETHYLENE	5-10%
CAS number: 156-60-5	EC number: 205-860-2
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Aquatic Chronic 3 - H412	

Permabond CSA - Liquid

N,N-DIMETHYL-PARA-TOLUIDINE	<1%
CAS number: 99-97-8	EC number: 202-805-4
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Drink a few glasses of water or milk. Do not induce vomiting. Get medical attention.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Inhalation	Vapours may cause drowsiness and dizziness.
Skin contact	Prolonged contact may cause redness, irritation and dry skin.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Avoid vomiting and stomach flushing because of the risk of aspiration.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Heating may generate flammable vapours. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
Hazardous combustion products	Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Permabond CSA - Liquid

Protective actions during firefighting Containers close to fire should be removed or cooled with water.

Special protective equipment for firefighters Wear self contained breathing apparatus and protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Remove or isolate all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. During application and drying, solvent vapours will be emitted. Use in a well ventilated area. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) Activator.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn. Gloves should conform to EN 374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Permabond CSA - Liquid

Other skin and body protection	Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower. Uniforms, coveralls, or a lab coat should be worn
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Use of good industrial hygiene practices is required.
Respiratory protection	Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	aromatic hydrocarbons
pH	Not applicable.
Melting point	Not known.
Initial boiling point and range	45 - 100°C
Flash point	~ -4°C
Evaporation rate	4.3
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.7
Solubility(ies)	Insoluble in water.
Auto-ignition temperature	Not available.
Viscosity	~ 0.7 mPa s @ 23°C

9.2. Other information

Other information	Not relevant.
--------------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	The following materials may react with the product: Strong oxidising agents.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	There are no known reactivity hazards associated with this product.
---	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

Permabond CSA - Liquid

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The toxicological properties of this product have not been fully evaluated. Do not ingest or inhale. Avoid direct contact with skin or eyes.

Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Irritating to skin. Repeated exposure may cause skin dryness or cracking. May cause sensitisation by skin contact.

Eye contact

Irritating and may cause redness and pain.

Toxicological information on ingredients.

HYDROCARBONS, C7, n-ALKANES, ISOALKANES, CYCLICS

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,800.0

Species Rat

ATE dermal (mg/kg) 2,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 23.3

Species Rat

Permabond CSA - Liquid

ATE inhalation (vapours
mg/l) 23.3

trans-DICHLOROETHYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 2,000.1

Species Rat

ATE oral (mg/kg) 2,000.1

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 5,000.0

Species Rabbit

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Acute toxicity inhalation
(LC₅₀ gases ppmV) 24,000.0

Species Rat

ATE inhalation (gases
ppm) 4,500.0

N,N-DIMETHYL-PARA-TOLUIDINE

Acute toxicity - oral

ATE oral (mg/kg) 100.0

Acute toxicity - dermal

ATE dermal (mg/kg) 300.0

Acute toxicity - inhalation

Acute toxicity inhalation
(LC₅₀ vapours mg/l) 3.19

ATE inhalation (vapours
mg/l) 3.19

Skin corrosion/irritation

Animal data Moderately irritating.

Serious eye damage/irritation

Serious eye
damage/irritation Moderately irritating.

Germ cell mutagenicity

Genotoxicity - in vitro Ames test This substance has no evidence of mutagenic properties.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Permabond CSA - Liquid

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C7, n-ALKANES, ISOALKANES, CYCLICS

Acute toxicity - fish	LL ₅₀ , 96 hours: > 13.4 mg/l, Onchorhynchus mykiss (Rainbow trout)
Acute toxicity - aquatic plants	NOELR, 72 hours: 6.3 mg/l, Pseudokirchneriella subcapitata
Acute toxicity - microorganisms	NOELR, 48 hours: 5.999 mg/l, Tetrahymena pyriformis
Chronic toxicity - fish early life stage	NOELR, 28 days: 1.534 mg/l, Onchorhynchus mykiss (Rainbow trout)
Chronic toxicity - aquatic invertebrates	NOELR, 21 days: 1 mg/l, Daphnia magna

trans-DICHLOROETHYLENE

Acute toxicity - aquatic invertebrates	NOEC, 48 hours: 110 mg/l, Daphnia magna LC ₅₀ , 48 hours: 220 - 290 mg/l, Daphnia magna
---	---

N,N-DIMETHYL-PARA-TOLUIDINE

Acute toxicity - fish	LC ₅₀ , 96 hours: 46 mg/l, Pimephales promelas (Fat-head Minnow)
------------------------------	---

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product contains organic solvents which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
Disposal methods	Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Containers should be thoroughly emptied before disposal because of the risk of an explosion.

Permabond CSA - Liquid

Waste class 14 06 03 other solvents and solvent mixtures

SECTION 14: Transport information

14.1. UN number

1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C7, n-Alkanes, isoalkanes,cyclics)

14.3. Transport hazard class(es)

3

Transport labels



14.4. Packing group

II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

Emergency Action Code 3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance Workplace Exposure Limits EH40.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

Permabond CSA - Liquid

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	26/07/2017
Revision	4
Supersedes date	05/03/2015
Hazard statements in full	H225 Highly flammable liquid and vapour. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H315 Causes skin irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.